

# PA-655/PA-622 AC/DC Current Probe



## SPECIFICATIONS:

FUNCTION/MODEL	PA-655
DC Accuracy Typical	$\pm 3\%$ : 30mA~5A peak at 200mV/A $\pm 4\%$ : 300mA~20A peak at 20mV/A $\pm 15\%$ : 20A~50A peak
Max. Working Voltage	300V CAT III
Max. Floating Voltage	600V CAT II
Frequency Range	DC-500KHz(-3dB)
Rise Time	0.7 us
Battery or Adaptor	9V NEDA 1604A, IEC DLR61 or PINTEK Specified Adaptor
Accessories	BP-250, MT-246N, Adaptor, Instruction Manual.

## ACCESSORIES:



# **PINTEK**

## **Pintek Electronics Co., Ltd**

2F No.32 Tai-Pen Rd., Shulin Dist., New Taipei City, Taiwan  
 Tel: 886-2-86859562~3 ; 886-2-86861898  
 Fax: 886-2-86852081 ; 886-2-86861114  
<http://www.pintek.com.tw>  
 E-Mail : [pintek@pintek.com.tw](mailto:pintek@pintek.com.tw) ; [pintek@ms26.hinet.net](mailto:pintek@ms26.hinet.net)

**CE**

SALES AGENT